

2730 Sheath Grounding Unit



The 2730 Sheath Grounding Unit (SGU) is a field installed unit designed to provide maximum protection against 60 Hz induced power line currents and high voltage transient surges on cable armors. The unit is an environmentally sealed combination maximum duty failsafe arrestor and a 60 Hz series pass Induced Voltage Filter (IVF). Recommended placement is every 1500m/4921 ft. on aerial plant and at every splice point on below grade installations.

Features

- Provides low impedance ground path for high transient voltages
- Provides low impedance ground path for 60 Hz induced voltages
- Compatible with fibre cable locate systems
- Designed for above or below grade use
- Rated at .5 amp continuous AC current
- Failsafe circuitry design
- Hybrid surge suppression circuitry
- UV resistant packaging

Specifications

ITEM	QUANTITY/SPECIFICATION	NOTES
Inputs		
Capacitance	< 30 pF	Line to ground
Protection		
DC Breakdown Voltage	300 - 500 VDC	
Impulse Breakdown	500v (Typical) at 100 v/μsec 750v (Max) at 100 v/μsec	
Impulse Current Rating	40,000 A	8x20μs impulsive, single cycle
AC Current Rating (Continuous)	0.5 A	
AC Current Rating (Momentary)	10 A	60Hz AC, 1s application
AC Voltage Rating (Continuous)	175 VAC	60Hz AC Continuous
Induced Voltage Filtering		
Voltage Reduction Ratio (typical)	7:1	VI/Vf
(Zsource = 200Ω, IF = 500 ma)		
Maximum Voltage (Continuous)	20 V	AC RMS
(5 min)	250 V	AC RMS
Clamping Voltage (typical)	15 V	AC RMS
Impedance (nominal)	30 Ω @ 60 Hz (I = 500 mA) 1200 Ω @ 30 Hz 7000 Ω @ 512 Hz	
Environmental		
Operating Temperature	-50°C to +85°C	
Range	-58°F to +185°F	
Placement Recommendation		
Aerial OSP	Every 1500 m / 4921 ft	
Below Grade OSP	Each Splice Location	
Model Number(s)		
	2730 SGU	Sheath Grounding Unit #10 leads
	2736 WGU	Sheath Grounding Unit #6 leads

PROVIDES LOW IMPEDANCE GROUND PATH FOR HIGH TRANSIENT VOLTAGES

PROVIDES LOW IMPEDANCE GROUND PATH FOR 60 HZ INDUCED VOLTAGES

COMPATIBLE WITH FIBRE CABLE LOCATE SYSTEMS

DESIGNED FOR ABOVE OR BELOW GRADE USE

RATED AT .5 AMP CONTINUOUS AC CURRENT

FAILSAFE CIRCUITRY DESIGN

HYBRID SURGE SUPPRESSION CIRCUITRY

UV RESISTANT PACKAGING

For more information on any of our products or services, please visit us on the web at:
www.norscan.com

30 PRAIRIE WAY
WINNIPEG, MB R2J 3J8
P: 204.233.9138
F: 204.233.9188
SALES@NORSCAN.COM
WWW.NORSCAN.COM

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

NORSCAN
Instruments Ltd.